



BROWNING BEARING COMPANY



30 mm x 62 mm x 16 mm skf 7206 bep bearing

Bearing No. 7206 bep

Size	62x30x16 mm
Bore Diameter	62 mm
Outer Diameter	30 mm
Width	16 mm
d	30 mm
D	62 mm
B	16 mm
d ₁	42.65 mm
d ₂	36.13 mm
D ₁	50.1 mm
a	27.3 mm
r _{1,2} - min.	1 mm
r _{3,4} - min.	0.6 mm
d _a - min.	35.6 mm
D _a - max.	56.4 mm
D _b - max.	57.8 mm
r _a - max.	1 mm
r _b - max.	0.6 mm
Basic dynamic load rating - C	22.5 kN
Basic static load rating - C ₀	14.3 kN
Fatigue load limit - P _u	0.61 kN
Reference speed	13000 r/min
Limiting speed	13000 r/min
Calculation factor - k _r	0.095
Calculation factor - k _a	1.4

7206 bep Bearing 2D drawings and 3D CAD models



BROWNING BEARING COMPANY

Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y ₀	0.52
Calculation factor - Y ₁	0.55
Calculation factor - Y ₂	0.93
Calculation factor - X	0.35
Calculation factor - Y ₀	0.26
Calculation factor - Y ₁	
Calculation factor - Y ₂	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.19
EAN	7316571410364
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 16MM



BROWNING BEARING COMPANY

	Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7206 BEP
Weight / LBS	0.414
Outside Diameter	2.441 Inch 62 Millimeter
Width	0.63 Inch 16 Millimeter
Bore	1.181 Inch 30 Millimeter
bore diameter:	30 mm
radial static load capacity:	14.3 kN
outside diameter:	62 mm
cage material:	Nylon
overall width:	16 mm
outer ring width:	16 mm
contact angle:	40 °
maximum rpm:	13000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	1 mm
radial dynamic load capacity:	22.5 kN
series:	72



BROWNING BEARING COMPANY

d_1	42.65 mm
d_2	36.13 mm
D_1	50.1 mm
$r_{1,2}$ min.	1 mm
$r_{3,4}$ min.	0.6 mm
d_a min.	35.6 mm
D_a max.	56.4 mm
D_b max.	57.8 mm
r_a max.	1 mm
r_b max.	0.6 mm
Basic dynamic load rating C	22.5 kN
Basic static load rating C_0	14.3 kN
Fatigue load limit P_u	0.61 kN
Calculation factor A	0.00377
Calculation factor k_r	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	0.2 kg