



# BROWNING BEARING COMPANY



80 mm x 110 mm x 16 mm skf 61916 bearing

Bearing No. 61916

61916 Bearing 2D drawings and 3D CAD models

Size	110x80x16 mm
Bore Diameter	110 mm
Outer Diameter	80 mm
Width	16 mm
d	80 mm
D	110 mm
B	16 mm
d <sub>1</sub>	89.8 mm
D <sub>2</sub>	102.2 mm
r <sub>1,2</sub> - min.	1 mm
d <sub>a</sub> - min.	84.6 mm
D <sub>a</sub> - max.	105 mm
r <sub>a</sub> - max.	1 mm
Basic dynamic load rating - C	25.1 kN
Basic static load rating - C <sub>0</sub>	20.4 kN
Fatigue load limit - P <sub>u</sub>	1 kN
Reference speed	12000 r/min
Limiting speed	7500 r/min
Calculation factor - k <sub>r</sub>	0.02
Calculation factor - f <sub>0</sub>	14
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.41



## BROWNING BEARING COMPANY

EAN	7316577122018
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	80MM Bore; 110MM Outside Diameter; 16MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	61916
Weight / LBS	0.9
Outside Diameter	4.331 Inch   110 Millimeter
Bore	3.15 Inch   80 Millimeter
Outer Race Width	0.63 Inch   16 Millimeter
bore diameter:	80 mm
static load capacity:	20.4 kN
outside diameter:	110 mm
precision rating:	Not Rated



## BROWNING BEARING COMPANY

overall width:	16 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	16 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	7500 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	25.1 kN
$d_1$	89.8 mm
$D_2$	102.2 mm
$r_{1,2}$ min.	1 mm
$d_a$ min.	84.6 mm
$D_a$ max.	105 mm
$r_a$ max.	1 mm
Basic dynamic load rating C	25.1 kN
Basic static load rating $C_0$	20.4 kN
Fatigue load limit $P_u$	1.02 kN
Calculation factor $k_r$	0.02
Calculation factor $f_0$	14
Mass bearing	0.38 kg